

Amendment to 09/837433 dated 6 January 2004

Page 2 of 13

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously presented) A method for varying a direction of a light beam passing through a micro-machined device, said method comprising
directing said light beam through a transparent membrane separating two refractive regions, each of said refractive regions comprising a fluid with a different refractive index, said membrane being attached at its perimeter to a fixed member; and,
inducing a deformation of said membrane, thereby increasing a thickness of a first one of said refractive regions and correspondingly decreasing a thickness of a second one of said refractive regions.
2. (Previously presented) A method as in claim 1, wherein said deformation is induced by electrostatic force.
3. (Previously presented) A method as in claim 1, wherein at least one of said refractive regions comprises a refractive liquid.
4. (Previously presented) A method as in claim 3, wherein said membrane is in tensile stress.
5. (Previously presented) A method as in claim 3, wherein said tensile stress is induced during fabrication of said membrane.
6. (Previously presented) A method as in claim 4, wherein the perimeter of said membrane is substantially circular.

Amendment to 09/837433 dated 6 January 2004

Page 3 of 13

7. (Previously presented) A method as in claim 4, wherein said membrane is one of a plurality of substantially identical membranes fabricated on one contiguous section of silicon wafer and each one of said plurality of membranes is capable of being deformed independently of any other one of said plurality of membranes.
8. (Previously presented) A method as in claim 7, wherein more than one of said plurality of membranes are in contact with a single body of refractive liquid.
9. (Previously presented) A method as in claim 1, comprising controlling the direction of the light beam passing through the micro-machined device using a feedback method.
10. (Previously presented) A method as in claim 9, wherein said feedback method comprises generating a signal indicative of one or more of: the direction of the light beam passing through the micro-machined device, an amount of said deformation, an amount of electrostatic force between said membrane and an electrode on said fixed member, and an amount of electrical capacitance between said membrane and said electrode.
11. (Previously presented) A method as in claim 10, wherein said feedback method comprises linearization of the deformation of said membrane.
12. (Previously presented) A method as in claim 11, wherein said linearization comprises using data from a look-up table.
13. (Previously presented) A method as in claim 12, wherein said look-up tables are programmed into memory cells resident on the same piece of contiguous silicon as said membrane.

Amendment to 09/837433 dated 6 January 2004

Page 4 of 13

14. (Previously presented) An adaptive lens in a micro-machined device, said adaptive lens comprising a deformable transparent membrane separating two refractive regions, each of said refractive regions comprising a fluid with a different refractive index, wherein an amount of deformation of said transparent membrane determines an amount of refraction caused to a light beam transmitted by said adaptive lens.
15. (Previously presented) An adaptive lens as in claim 14, wherein deformation of said membrane is induced by electrostatic force.
16. (Previously presented) An adaptive lens as in claim 14, wherein at least one of said refractive regions comprises a refractive liquid.
17. (Previously presented) An adaptive lens as in claim 16, wherein said membrane is in tensile stress.
18. (Previously presented) An adaptive lens as in claim 17, wherein said tensile stress is induced during fabrication of said membrane.
19. (Previously presented) An adaptive lens as in claim 16, wherein said membrane is substantially circular.
20. (Previously presented) An adaptive lens as in claim 14, wherein said deformable transparent membrane is one of a plurality of substantially identical membranes fabricated on one contiguous section of silicon wafer and each one of said plurality of membranes is capable of being deformed independently of any other one of said plurality of membranes.
21. (Previously presented) An adaptive lens as in claim 20, wherein more than one of said plurality of membranes are in contact with a single body of refractive liquid.

Amendment to 09/837433-dated 6 January 2004Page 5 of 13

22. (Previously presented) An adaptive lens within a micro-machined device, said adaptive lens comprising of a transparent membrane attached at its perimeter to a fixed member and
 - a. said membrane separating two refractive regions of differing refractive index, and
 - b. said membrane being capable of changing its curvature in response to an electrical control signal, the degree of refraction of said adaptive lens being controlled by said curvature.
23. (Previously presented) An adaptive lens as in claim 22, wherein at least one of said refractive regions comprises a refractive liquid.
24. (Previously presented) An adaptive lens as in claim 23, wherein said membrane is in tensile stress.
25. (Previously presented) An adaptive lens as in claim 22, wherein said membrane is one of a plurality of substantially identical membranes fabricated on one contiguous section of silicon wafer, said membrane being capable of being deformed independently of any other one of said multiplicity of membranes.
26. (Previously presented) An adaptive lens as in claim 25, wherein more than one of said plurality of substantially identical membranes are in contact with the same body of refractive liquid.
27. (Previously presented) An adaptive lens as in claim 22 wherein said degree of refraction is controlled via a feedback mechanism.
28. (Previously presented) An adaptive lens as in claim 27, wherein said feedback mechanism comprises a feedback

Amendment to 09/837433 dated 6 January 2004

Page 6 of 13

sensor, which indicates one or more of: said degree of refraction, an amount of said curvature, an amount of electrostatic force between said membrane and an electrode on said fixed member, and an amount of electrical capacitance between said membrane and said electrode.

29. (Previously presented) An adaptive lens as in claim 28 wherein said feedback mechanism comprises a linearization means to linearize said adaptive lens.
30. (Previously presented) An adaptive lens as in claim 29 wherein said linearization means comprises look-up tables.
31. (Previously presented) An adaptive lens as in claim 30 wherein said look-up tables are programmed into memory cells resident on the same piece of contiguous silicon as said adaptive lens.
32. (Canceled)
33. (Currently amended) ~~An adaptive lens according to claim 32, A micro-electromechanical adaptive lens comprising a deformable transparent membrane attached at its perimeter to a substrate, wherein an amount of deformation of the membrane determines an amount of refraction of a light beam transmitted through the adaptive lens,~~ wherein the membrane extends over a cavity in the substrate and, when deformed, the membrane curves into the cavity.
34. (Previously presented) An adaptive lens according to claim 33, wherein the membrane separates a first region and a second region, each of the first and second regions comprising a fluid with a different refractive index.
35. (Previously presented) An adaptive lens according to claim 33, wherein the cavity contains a liquid which has

Amendment to 09/837433 dated 6 January 2004

Page 7 of 13

a refractive index different than that of a fluid on an opposing side of the membrane.

36. (Previously presented) An adaptive lens according to claim 33 comprising an electrode located in a vicinity of the membrane, wherein the amount of deformation of the membrane is dependent on a magnitude of an electric field applied between the electrode and the membrane.
37. (Previously presented) An adaptive lens according to claim 36, wherein the electrode is located inside the cavity.
38. (Previously presented) An adaptive lens according to claim 37, wherein the electrode is substantially transparent.
39. (Previously presented) An adaptive lens according to claim 36, wherein the membrane comprises a conductive layer and an insulating layer.
40. (Previously presented) An adaptive lens according to claim 39, wherein the insulating layer is located between the electrode and the conductive layer.
41. (Previously presented) An adaptive lens according to claim 36, wherein, when the magnitude of the electric field is zero, the membrane is substantially flat.
42. (Previously presented) An adaptive lens according to claim 36, comprising a feedback unit, wherein the feedback unit is connected to receive a control signal indicative of a desired amount of refraction and at least one of: a measured value of the amount of refraction; a measured value of the amount of deformation; a measured value of the size of the electric field; and, a measured value of an amount of capacitance between the membrane and the electrode; and wherein the feedback unit is connected to output a signal that controls the magnitude

Amendment to 09/837433 dated 6 January 2004

Page 8 of 13

of the electric field, to produce the desired amount of refraction.

43. (Previously presented) An adaptive lens according to claim 42, wherein the feedback unit comprises a linearization module having at least one look-up table stored in a memory.
44. (Previously presented) An adaptive lens according to claim 43, wherein the memory comprises memory cells on the substrate.
45. (Currently amended) ~~An adaptive lens according to claim 32, A micro-electromechanical adaptive lens comprising a deformable transparent membrane attached at its perimeter to a substrate, wherein an amount of deformation of the membrane determines an amount of refraction of a light beam transmitted through the adaptive lens, wherein the membrane is under tensile stress.~~
46. (Previously presented) An adaptive lens according to claim 45, wherein the tensile stress is induced during fabrication of the membrane.
47. (Currently amended) ~~An adaptive lens according to claim 32, A micro-electromechanical adaptive lens comprising a deformable transparent membrane attached at its perimeter to a substrate, wherein an amount of deformation of the membrane determines an amount of refraction of a light beam transmitted through the adaptive lens, wherein the perimeter of the membrane is substantially circular.~~
48. (Currently amended) A plurality of substantially similar micro-electromechanical adaptive lenses each comprising a deformable transparent membrane attached at its perimeter to a substrate, wherein an amount of deformation of the membrane determines an amount of refraction of a light beam transmitted through the adaptive lens, according to claim 32, each one of the adaptive lenses fabricated in a

Amendment to 09/837433 dated 6 January 2004

Page 9 of 13

single substrate and comprising an independently deformable transparent membrane.

49. (Previously presented) A plurality of adaptive lenses according to claim 48, wherein the independently deformable transparent membranes extend over a single cavity in the substrate and, when deformed, each membrane curves into the cavity.
50. (Previously presented) A plurality of adaptive lenses according to claim 49, wherein the cavity contains a body of refractive liquid and each membrane is in contact with the body of refractive liquid.
51. (Currently amended) ~~An adaptive lens according to claim 32, A micro-electromechanical adaptive lens comprising a deformable transparent membrane attached at its perimeter to a substrate, wherein an amount of deformation of the membrane determines an amount of refraction of a light beam transmitted through the adaptive lens,~~ wherein the membrane separates a first region and a second region, each of the first and second regions comprising a fluid having a different refractive index.
52. (Currently amended) ~~An adaptive lens according to claim 32 A micro-electromechanical adaptive lens comprising a deformable transparent membrane attached at its perimeter to a substrate, wherein an amount of deformation of the membrane determines an amount of refraction of a light beam transmitted through the adaptive lens,~~ comprising an electrode located in a vicinity of the membrane, wherein the amount of deformation of the membrane is determined by an electric field applied between the electrode and the membrane.
53. (Canceled)
54. (Previously presented) ~~A method according to claim 53, A method for varying an amount of refraction of a light~~

Amendment to 09/837433 dated 6 January 2004

Page 10 of 13

beam transmitted by a micro-electromechanical adaptive lens, the method comprising:

providing a deformable transparent membrane, attached at its perimeter to a substrate; and

inducing a deformation of the membrane, wherein an amount of the deformation of the membrane determines the amount of refraction of the light beam transmitted by the adaptive lens, wherein inducing a deformation of the membrane comprises curving the membrane into a cavity formed in the substrate.

55. (Previously presented) A method according to claim 54, wherein the membrane separates a first region and a second region, each of which comprises a fluid with a different refractive index, and wherein deforming the membrane comprises decreasing a thickness of the second region.
56. (Previously presented) A method according to claim 55, wherein the second region comprises a refractive liquid.
57. (Previously presented) A method according to claim 54, wherein inducing a deformation of the membrane comprises applying an electrostatic force to the membrane.
58. (Previously presented) A method according to claim 57, wherein the amount of deformation of the membrane is dependent on a magnitude of the electrostatic force.
59. (Previously presented) A method according to claim 58, wherein, when the magnitude of the electrostatic force is zero, the membrane is substantially flat.
60. (Previously presented) A method according to claim 58 comprising controlling the amount of refraction of the light beam by:
- receiving a control signal indicative of a desired amount of refraction;

Amendment to 09/837433 dated 6 January 2004

Page 11 of 13

measuring at least one measured value from among:
the amount of refraction; the amount of deformation; the
magnitude of the electrostatic force; and a capacitance
associated with the electrostatic force;

generating an output signal that determines the
magnitude of the electric field to produce the desired
amount of refraction based on the control signal and the
at least one measured value.

61. (Previously presented) A method according to claim 60
comprising linearizing the deformation of the membrane.

62. (Currently amended) ~~A method according to claim 53~~ A
method for varying an amount of refraction of a light
beam transmitted by a micro-electromechanical adaptive
lens, the method comprising:

providing a deformable transparent membrane,
attached at its perimeter to a substrate; and

inducing a deformation of the membrane, wherein an
amount of the deformation of the membrane determines the
amount of refraction of the light beam transmitted by the
adaptive lens, comprising maintaining the membrane under
tensile stress.

63. (Currently amended) ~~A method according to claim 53;~~ A
method for varying an amount of refraction of a light
beam transmitted by a micro-electromechanical adaptive
lens, the method comprising:

providing a deformable transparent membrane,
attached at its perimeter to a substrate; and

inducing a deformation of the membrane, wherein an
amount of the deformation of the membrane determines the
amount of refraction of the light beam transmitted by the
adaptive lens, wherein the membrane separates a first
region and a second region, each of which comprises a
fluid with a different refractive index, and wherein
deforming the membrane comprises decreasing a thickness
of the second region.

Amendment to 09/837433 dated 6 January 2004

Page 12 of 13

64. (Currently amended) ~~A method according to claim 53, A method for varying an amount of refraction of a light beam transmitted by a micro-electromechanical adaptive lens, the method comprising:~~
- ~~providing a deformable transparent membrane, attached at its perimeter to a substrate; and~~
- ~~inducing a deformation of the membrane, wherein an amount of the deformation of the membrane determines the amount of refraction of the light beam transmitted by the adaptive lens, wherein inducing a deformation of the membrane comprises applying an electrostatic force to the membrane.~~
65. (Previously presented) An adaptive lens comprising a deformable transparent membrane spaced apart from a transparent base and a transparent liquid having an index of refraction different from that of a fluid on a side of the membrane away from the base, the liquid located between the membrane and the base.